

ARY cable suspended

canopy trim

049-521151XF 005-3521018 002-90732



Project / Type
Notes
Count / Date



General

Ceiling , Suspended
special colours
Canopy jet black
IP20
791 lm
fixture 94 lm/W ¹

LED

3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 100 , R _f : 90 , R _{f(1-5)} : 87
MR 0.59
MDER 0.54

Optical

flood
beam angle 44°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

non DIM
220-240 V
system 11.2 W
fixture 8.4 W
18 Vf
500 mA
PC2

Physical


suspension 2000 mm with hook
diameter 47 mm
height 110 mm
0.57 kg

Cutout

diameter 65 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 70 mm

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)


Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Product drawing



Installation instructions



Lighting calculator

