

# ARY cable suspended canopy surface

049-5211518F 005-2602198



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL 9005 <sup>1</sup>

Canopy jet black

IP20

791 lm

fixture 94 lm/W<sup>2</sup>

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-5)</sub>: 87

MR 0.59

MDER 0.54

Optical

flood

beam angle 44°

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

Electrical

Casambi

220-240 V

system 11.2 W

fixture 8.4 W

18 Vf

500 mA

PC2

Physical


suspension 2000 mm with hook

diameter 47 mm

height 110 mm

0.4 kg

## Light distribution



flood 44°			
h (m)	EO° (lx)	ø (m)	
1	1470	0.82	
2	370	1.64	
3	160	2.45	
4	90	3.27	
5	60	4.09	

## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

