

ARY cable suspended canopy surface

049-5211517M 005-2602117



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended
 white , RAL9016 ¹
 Canopy traffic white
 IP20
 739 lm

LED

3000 K
 CRI ≥ 90
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 100 , R_f: 90 , R₍₁₋₁₅₎: 87
 MR 0.59
 MDER 0.54

Optical

medium
 beam angle 25°

Electrical


non DIM
 11.2 W
 PC2 220-240V
 66 lm/W

Physical

suspension 2000 mm with hook
 diameter 47 mm
 height 110 mm
 0.57 kg

Decorative suspended luminaire in aluminium; surface white powder coated; pendant fitting with 2000mm suspension, incl. feed (white), can be individually shortened, incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Product drawing



¹ RAL code

Installation instructions



Lighting calculator



[049-5211517M 005-2602117] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

27.09.2024