

ARY cable suspended

canopy trim

049-5111618M 005-3521018 002-90733



Project / Type

Notes

Count / Date



220-240V

UGR ≤ 10

cd/m^2
 ≤ 1500

CRI ≥ 90

General

Ceiling , Suspended

black , RAL9005 ¹

Canopy jet black

IP20

739 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

$R_g: 99$, $R_f: 89$, $R_{f(1-15)}: 87$

MR 0.81

MDER 0.73

Optical

medium

beam angle 25°

$\text{PstLM} \leq 1.0$ ²

$\text{SVM} \leq 0.4$ ²

Electrical

DALI-2

11.2 W

PC2 220-240V

66 lm/W

1 DALI Addr.

Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.5 kg

Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Product drawing



Installation instructions



Lighting calculator

