

ARY cable suspended canopy surface

049-5111618F 005-2602198



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



flood 44°

| h (m) | EO ² (lx) | ø (m) |
|-------|----------------------|-------|
| 1 | 1470 | 0.82 |
| 2 | 370 | 1.64 |
| 3 | 160 | 2.45 |
| 4 | 90 | 3.27 |
| 5 | 60 | 4.09 |

Product drawing



220-240V

UGR
 ≤ 16

cd/m²
 ≤ 1500

CRI
 ≥ 90

General

Ceiling , Suspended

black , RAL9005 ¹

Canopy jet black

IP20

791 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_r: 89 , R_{t(1-5)}: 87

MR 0.81

MDER 0.73

Optical

flood

beam angle 44°

Electrical

Casambi

11.2 W

PC2 220-240V

71 lm/W

Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.3 kg

¹ RAL code

Installation instructions



Lighting calculator

