

ARY cable suspended canopy surface

049-5111618F 005-2602198



Project / Type

Notes

Count / Date



General

Ceiling , Suspended
 black , RAL 9005 ¹
 Canopy jet black
 IP20
 791 lm
 fixture 94 lm/W²

LED

4000 K
 CRI ≥ 90
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 99 , R_f: 89 , R₍₁₋₁₅₎: 87
 MR 0.81
 MDER 0.73

Optical

flood
 beam angle 44°
 PstLM ≤ 1.0 ³
 SVM ≤ 0.4 ³

Electrical

Casambi
 220-240 V
 system 11.2 W
 fixture 8.4 W
 18 Vf
 500 mA
 PC2

Physical

suspension 1500 mm
 diameter 47 mm
 height 110 mm
 0.3 kg


¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2; 220-240 V; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



flood 44°

h (m)	E0 ³ (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Product drawing



Installation instructions



Lighting calculator

