

# ARY cable suspended canopy surface

049-5111618F 005-2602118



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL 9005 <sup>1</sup>

Canopy jet black

IP20

791 lm

fixture 94 lm/W<sup>2</sup>

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 89 , R<sub>(1-15)</sub>: 87

MR 0.81

MDER 0.73

Optical

flood

beam angle 44°

Electrical

non DIM

220-240 V

system 11.2 W

fixture 8.4 W

18 Vf

500 mA

PC2

Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.46 kg

<sup>1</sup> RAL code

<sup>2</sup> incl. consideration of optical losses & internal control unit losses

## Light distribution



| flood 44° |          |       |
|-----------|----------|-------|
| h (m)     | E0° (lx) | ø (m) |
| 1         | 1470     | 0.82  |
| 2         | 370      | 1.64  |
| 3         | 160      | 2.45  |
| 4         | 90       | 3.27  |
| 5         | 60       | 4.09  |

## Product drawing



Installation instructions

Lighting calculator

