

ARY adjustable rod suspended canopy surface

049-5131618F 005-2601118



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

tilt max 90° _____

rotation 265° _____

black , RAL9005 ¹ _____

Canopy jet black _____

IP20 _____

791 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 89 , R_{t(1-5)}: 87 _____

MR 0.81 _____

MDER 0.73 _____

Optical

flood _____

beam angle 44° _____

Electrical

non DIM _____

system 11.2 W _____

inset 8.4 W _____

500 mA _____

PC2 220-240V _____

system 71 lm/W² _____

inset 94 lm/W³ _____

Physical

rod 1500 mm _____

diameter 47 mm _____

height 110 mm _____


0.61 kg _____

¹ RAL code

² incl. optical losses and the efficiency of the operating device (converter)

³ incl. optical losses

Light distribution



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Product drawing



Installation instructions Lighting calculator

