

ARY adjustable rod suspended

canopy trimless

049-513151XM 005-3512017 002-90733



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

tilt max 90° _____

rotation 265° _____

special colours _____

Canopy traffic white _____

IP20 _____

739 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 90 , R₍₁₋₁₅₎: 87 _____

MR 0.59 _____

MDER 0.54 _____

Optical

medium _____

beam angle 25° _____

PstLM ≤ 1.0 ¹ _____

SVM ≤ 0.4 ¹ _____

Electrical

DALI-2 _____

11.2 W _____

PC2 220-240V _____

66 lm/W _____

1 DALI Addr. _____

Physical

rod 1500 mm _____

diameter 47 mm _____

height 110 mm _____

0.61 kg _____

Cutout

diameter 65 mm _____


min. ceiling thickness 9 mm _____

max. ceiling thickness 25 mm _____

recessed depth 130 mm _____

¹ Value of containing product at full load (undimmed)

Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Product drawing



Installation instructions



Lighting calculator

