

ARY rod suspended canopy surface

049-5121517F 005-2601137



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Suspended _____
 white , RAL 9016 ¹ _____
 Canopy traffic white _____
 IP20 _____
 791 lm _____
 fixture 94 lm/W² _____

LED

3000 K _____
 CRI ≥ 90 _____
 L90 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 100 , R_f: 90 , R₍₁₋₁₅₎: 87 _____
 MR 0.59 _____
 MDER 0.54 _____

Optical

flood _____
 beam angle 44° _____
 PstLM ≤ 1.0 ³ _____
 SVM ≤ 0.4 ³ _____

Electrical

DALI-2 _____
 220-240 V _____
 system 11.2 W _____
 fixture 8.4 W _____
 18 Vf _____
 500 mA _____
 PC2 _____
 1 DALI Addr. _____

Physical

rod 1500 mm _____
 diameter 47 mm _____
 height 110 mm _____
 0.6 kg _____

¹ RAL code


² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

³ Value of containing product at full load (undimmed)



Decorative suspended luminaire in aluminium; surface white powder coated; height adjustable U-profile pendant rod suspension (white) 1500mm, feed in U-profile; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC2; 220-240 V; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

Product drawing



Installation instructions



Lighting calculator

