

# ARY cable suspended canopy surface

049-5111517M 005-2602197



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface white powder coated; pendant fitting with 1500mm suspension, incl. feed (white), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



medium 25°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Product drawing



## General

Ceiling , Suspended

white , RAL9016 <sup>1</sup>

Canopy traffic white

IP20

739 lm

## LED

3000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87

MR 0.59

MDER 0.54

## Optical

medium

beam angle 25°

## Electrical

Casambi

system 11.2 W

inset 8.4 W

500 mA

PC2 220-240V

system 66 lm/W<sup>2</sup>

inset 88 lm/W<sup>3</sup>

## Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.3 kg

<sup>1</sup> RAL code

<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>3</sup> incl. optical losses

## Installation instructions



## Lighting calculator

