

# ARY cable suspended

canopy trim

049-511141XM 005-3521018 002-90732



Project / Type

Notes

Count / Date



220-240V

UGR ≤ 10

cd/m² ≤ 1500

CRI ≥ 90

### General

Ceiling , Suspended

special colours

Canopy jet black

IP20

642 lm

### LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.54

MDER 0.49

### Optical

medium

beam angle 25°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

### Electrical

non DIM

11.2 W

PC2 220-240V

57 lm/W

### Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.47 kg

### Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 70 mm

<sup>1</sup> Value of containing product at full load (undimmed)

### Light distribution



medium 25°

h (m)	E0° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

### Product drawing



### Installation instructions



### Lighting calculator

