

# ARY cable suspended

canopy trimless

049-511141XM 005-3511017 002-90733



Project / Type

Notes

Count / Date



### General

Ceiling , Suspended

special colours

Canopy traffic white

IP20

642 lm

### LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.54

MDER 0.49

### Optical

medium

beam angle 25°

PstLM ≤ 1.0<sup>1</sup>

SVM ≤ 0.4<sup>1</sup>

### Electrical

DALI-2

system 11.2 W

inset 8.4 W

500 mA

PC2 220-240V

system 57 lm/W<sup>2</sup>

inset 76 lm/W<sup>3</sup>

1 DALI Addr.

### Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.46 kg

### Cutout


diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

### Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

### Product drawing

