

# ARY cable suspended canopy surface

049-511141XM 005-2602198



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface special colours powder coated; pendant fitting with 1500mm suspension, incl. feed (special colours), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



medium 25°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 2780     | 0.44  |
| 2     | 690      | 0.89  |
| 3     | 310      | 1.33  |
| 4     | 170      | 1.78  |
| 5     | 110      | 2.22  |

## Product drawing



220-240V

UGR  $\leq 10$

$\text{cd/m}^2$   $\leq 1500$

CRI  $\geq 90$

## General

Ceiling , Suspended

special colours

Canopy jet black

IP20

642 lm

## LED

2700 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89

MR 0.54

MDER 0.49

## Optical

medium

beam angle 25°

## Electrical

Casambi

11.2 W

PC2 220-240V

57 lm/W

## Physical

suspension 1500 mm

diameter 47 mm

height 110 mm

0.3 kg

## Installation instructions



## Lighting calculator



# ARY cable suspended canopy surface

049-511141XM 005-2602198



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000            | 40 000                          | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF               | 0.97                         | 0.96   | 0.95              | 0.93                            | 0.92   |
| LSF                | 1                            | 1      | 1                 | 1                               | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> | Room Surface Maintenance Factor |        |
| MF                 | Maintenance Factor           |        | LLMF              | Lamp Lumens Maintenance Factor  |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF               | Lamp Survival Faktor            |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Components

### CANOPY

| TYPE             | COLOUR    | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|-----------|--------|-------------------|
| 500 mA   Casambi | jet black | 115    | 005-2602198       |



## Mounting accessories

### RING CEILING MOUNTED

| COLOUR        | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 50     | 050-0510217       |
| jet black     | 50     | 050-0510218       |



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

| TYPE  | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------|------------|-------------------|
| 160 W | 72-90-63   | 005-6520210       |



### DIN RAIL LED DRIVER

| TYPE                           | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------------------------------|------------|-------------------|
| DALI-2   200-1050 mA   2 x 42W | 36-88-59   | 005-6121030       |



## Other accessories

### SPECIAL MOUNTING TOOL

| TYPE   | Ø (MM) | ARTICLE NUMBER(S) |
|--|--------|-------------------|
| necessary to install mounting housing trimless | 100    | 063-8912110       |



# ARY cable suspended canopy surface

049-511141XM 005-2602198



Project / Type

Notes

Count / Date

## Optical accessories

### SHADE 300

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 300    | 049-593311B       |
| velvet beige     | 300    | 049-593311C       |
| woodpecker olive | 300    | 049-593311G       |
| kingfisher grey  | 300    | 049-593311L       |
| madeira brown    | 300    | 049-593311T       |
| signal white     | 300    | 049-593311W       |



### SHADE 400

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 400    | 049-593411B       |
| velvet beige     | 400    | 049-593411C       |
| woodpecker olive | 400    | 049-593411G       |
| kingfisher grey  | 400    | 049-593411L       |
| madeira brown    | 400    | 049-593411T       |
| signal white     | 400    | 049-593411W       |



### SHADE 500

| COLOUR           | Ø (MM) | ARTICLE NUMBER(S) |
|------------------|--------|-------------------|
| signal black     | 500    | 049-593511B       |
| velvet beige     | 500    | 049-593511C       |
| woodpecker olive | 500    | 049-593511G       |
| kingfisher grey  | 500    | 049-593511L       |
| madeira brown    | 500    | 049-593511T       |
| signal white     | 500    | 049-593511W       |



## Optical accessories

### OVAL LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 42     | 007-1965880       |



### SOFT LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 42     | 007-1965980       |



### WALLWASHER LENS

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 42     | 007-1965780       |

