

ARY cable suspended

canopy trimless

049-5111418M 005-3511017 002-90733



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

black , RAL9005 ¹ _____

Canopy traffic white _____

IP20 _____

642 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89 _____

MR 0.54 _____

MDER 0.49 _____

Optical

medium _____

beam angle 25° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

system 11.2 W _____

inset 8.4 W _____

500 mA _____

PC2 220-240V _____

system 57 lm/W³ _____

inset 76 lm/W⁴ _____

1 DALI Addr. _____

Physical

suspension 1500 mm _____

diameter 47 mm _____

height 110 mm _____

0.46 kg _____

Cutout


diameter 65 mm _____

min. ceiling thickness 9 mm _____

max. ceiling thickness 25 mm _____

recessed depth 130 mm _____

Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2780	0.44
2	690	0.89
3	310	1.33
4	170	1.78
5	110	2.22

Product drawing

