

# SASSO 60 round wallwasher

semi-recessed

048-37016174A 002-90771



Project / Type

Notes

Count / Date



General
Ceiling , Semi-Recessed
rotation 360°
white , RAL9016/matt silver <sup>1</sup>
Inner colour matt silver
IP20
766 lm

LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 94 , R <sub>f</sub> : 87 , R <sub>f(1-15)</sub> : 86
MR 0.8
MDER 0.72

Optical
wallwasher
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


Electrical
non DIM
220-240 V
system 9.7 W
inset 8.3 W
27 Vf
300 mA
PC2
system 79 lm/W <sup>3</sup>
inset 93 lm/W <sup>3</sup>

Physical
diameter 72 mm
height 75 mm
0.46 kg

Cutout
diameter 60 mm
recessed depth 85 mm

Cylindrical semi-recessed spotlight made of aluminium; surface white powder coated; Inner colour lacquered in matt silver; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Installation instructions



## Lighting calculator

