

SASSO 100 round direct / indirect

wall
048-346061190



Project / Type

Notes

Count / Date



220-240V

X-PERT

UGR

≤22

CRI

≥90

X-PERT

General

Wall , Surface

black , RAL9005/gold ¹

Inner colour gold

IP20

indirect 1200 lm

direct 1200 lm

total 2400 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₅₎: 89

MR 0.81

MDER 0.74

Optical


opal (lambertsch)

PstLM ≤ 1.0 ²


SVM ≤ 0.4 ²

Cylindrical wall surface mounted luminaire made of aluminium; surface black (housing/light inset); passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; homogeneous wall or ceiling illumination through uniform light distribution; direct/indirect light distribution; degree of protection IP20; PC1 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical

non DIM

41 W

PC1 220-240V

59 lm/W

inset 69 lm/W

Physical

length 113 mm

width 103 mm

height 183 mm

1.1 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

