

# SASSO 100 round direct / indirect

wall  
048-346053190



Project / Type

Notes

Count / Date



### General

Wall , Surface

black , RAL9005/gold <sup>1</sup>

Inner colour gold

IP20

indirect 1130 lm

direct 1130 lm

total 2260 lm

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

### Optical

opal (lambertsch)

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

system 41 W

PC1 220-240V

system 55 lm/W<sup>3</sup>

inset 66 lm/W<sup>4</sup>

1 DALI Addr.

### Physical

length 113 mm


width 103 mm

height 183 mm


1.1 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

### Light distribution



### Product drawing



### Installation instructions

