

SASSO 100 round direct / indirect

wall
048-346043190



Project / Type

Notes

Count / Date



| |
|-----------------------------------|
| General |
| Wall , Surface |
| black , RAL9005/gold ¹ |
| Inner colour gold |
| IP20 |
| indirect 1070 lm |
| direct 1070 lm |
| total 2140 lm |


| |
|---|
| LED |
| 2700 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.53 |
| MDER 0.48 |

| |
|--------------------------|
| Optical |
| opal (lambertsch) |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |


Cylindrical wall surface mounted luminaire made of aluminium; surface black (housing/light inset); passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; homogeneous wall or ceiling illumination through uniform light distribution; direct/indirect light distribution; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

| |
|---------------|
| Electrical |
| DALI-2 |
| 41 W |
| PC1 220-240V |
| 52 lm/W |
| inset 62 lm/W |
| 1 DALI Addr. |

Light distribution



Product drawing



| |
|---------------|
| Physical |
| length 113 mm |
| width 103 mm |
| height 183 mm |
| 1.1 kg |

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

