

# SASSO 100 round downlight

suspended

048-34204374F



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended  
white , RAL9016/matt silver <sup>1</sup>  
Inner colour matt silver  
IP20  
1560 lm

## LED

2700 K  
CRI  $\geq 90$   
L80 / 50000 h  
initial MacAdam  $\leq 2$  SDCM  
R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89  
MR 0.53  
MDER 0.48

## Optical

flood  
beam angle 44°  
UGR  $< 16$  ,  $\geq 65^\circ$   $< 3000$  cd/m<sup>2</sup>  
PstLM  $\leq 1.0$  <sup>2</sup>  
SVM  $\leq 0.4$  <sup>2</sup>

## Electrical


DALI-2  
system 20.2 W  
PC1 220-240V  
system 77 lm/W<sup>3</sup>  
inset 91 lm/W<sup>4</sup>  
1 DALI Addr.

## Physical

diameter 100 mm  
height 115 mm  
1.3 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

