

SASSO 60 round adjustable

ceiling
048-31106317M



Project / Type _____

Notes _____

Count / Date _____




General	
Ceiling , Surface	_____
tilt max 30°	_____
rotation 360°	_____
black , RAL9005/white ¹	_____
Inner colour white	_____
IP20	_____
876 lm	_____

LED	
4000 K	_____
CRI ≥ 90	_____
L80 / 50000 h	_____
initial MacAdam ≤ 2 SDCM	_____
R _g : 97 , R _r : 90 , R ₍₁₋₁₅₎ : 89	_____
MR 0.81	_____
MDER 0.74	_____


Optical	
medium	_____
beam angle 22°	_____
UGR < 19	_____

Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface black powder coated; Inner colour lacquered in white; 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 22° beam; UGR ≤ 19; degree of protection IP20; PC1; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical	
DALI-2	_____
220-240 V	_____
system 10.4 W	_____
PC1	_____
system 84 lm/W ²	_____
1 DALI Addr.	_____

Physical	
diameter 72 mm	_____
height 108 mm	_____
0.5 kg	_____

¹ RAL code
² incl. optical losses and the efficiency of the operating device (converter)

Installation instructions



Lighting calculator

