

# SASSO 60 base square downlight 1 lamp

ceiling

048-30304379F



Project / Type

Notes

Count / Date



## General

Ceiling , Surface

white , RAL9016/gold <sup>1</sup>

Inner colour gold

IP20

811 lm

## LED

2700 K

CRI  $\geq$  90

L80 / 50000 h

initial MacAdam  $\leq$  2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optical

flood

beam angle 41°

UGR  $< 16$  ,  $\geq 65^\circ$   $< 3000$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$  <sup>2</sup>

SVM  $\leq 0.4$  <sup>2</sup>

## Electrical

DALI-2

system 10.3 W

PC1 220-240V

system 79 lm/W<sup>3</sup>

inset 93 lm/W<sup>4</sup>

## Physical

length 180 mm

width 80 mm

height 81 mm


0.5 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>4</sup> incl. optical losses

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

