SASSO 100 square wallwasher

trim

048-2750614A 048-2797317 002-90776

Project / Type

Notes

Count / Date

220-240V X-PERT X-PERT

Recessed square spotlight in die-cast aluminium; 1 lamp; surface matt silver; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 70% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed
matt silver
Mounting set traffic white
IP20
2270 lm

LED

4000 K
CRI ≥ 90
L70 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 94 , R_f: 87 , R_{f1-15}: 86
MR 0.8
MDER 0.72

Optical

wallwasher
PstLM ≤ 1.0 [1]
SVM ≤ 0.4 [1]

Electrical

DALI-2
29.4 W
inset 25.0 W
36 Vf
350 mA
PC2 220-240V
77 lm/W

Physical

trim
length 118 mm
width 118 mm
height 96 mm
0.73 kg

Cutout

length 112 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 120 mm

[1] Value of containing product at full load (undimmed)

Installation instructions

Lighting calculator

['048-2750614A 048-2797317 002-90776'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com