

SASSO 100 square adjustable

trim

048-2730514F 048-279731G 002-90776



Project / Type

Notes

Count / Date



General

Ceiling , Recessed
 tilt max 30°
 matt silver
 Mounting set silver-grey
 front IP40 , back IP20
 2190 lm

LED

3000 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 100 , R_f: 91 , R_{f(1-15)}: 88
 MR 0.59
 MDER 0.53

Optical

flood
 beam angle 44°
 UGR < 16 , ≥65° <3000 cd/m²
 P_{stLM} ≤ 1.0¹
 SVM ≤ 0.4¹

Electrical

DALI-2
 29.2 W
 inset 24.8 W
 36 Vf
 700 mA
 PC2 220-240V
 75 lm/W
 1 DALI Addr.

Physical

trim
 length 118 mm
 width 118 mm
 height 95 mm
 0.53 kg


Cutout

length 112 mm
 width 112 mm
 min. ceiling thickness 2 mm
 max. ceiling thickness 25 mm
 recessed depth 100 mm


¹ Value of containing product at full load (undimmed)

Recessed square spotlight in die-cast aluminium; 1 lamp; surface matt silver; 30° tiltable; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim silver-grey; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 44° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

