

SASSO 60 emergency light selftest

trim
048-2693227 048-2696317



Project / Type

Notes

Count / Date



General
Ceiling , Recessed
rotation 360°
white , RAL 9016 ¹
Mounting set traffic white
IP20
206 ² , 208 ³ , 217 ⁴ lm

LED
6500 K
CRI ≥ 80


Optical
emergency light
beam angle 21° ² , 103°x25° ³ , 149°x150° ⁴

Electrical
220-240 V
system 1.0 W
system 206 ² , 208 ³ , 217 ⁴ lm/W ⁵
PC2


Round LED emergency light inset; surface lacquered in white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; selftest with status LED; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2; light source not replaceable;

Physical
trim
diameter 80 mm
height 94 mm
0.35 kg

Light distribution



Product drawing



Cutout
diameter 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens
⁵ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

