

# SASSO 60 emergency light basic

trimless exposed concrete  
048-2693211 048-2695210



Project / Type




Notes

Count / Date





Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; with test button; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;

## Light distribution



## Product drawing



## General

Ceiling , Recessed

rotation 360°

black , RAL9005 <sup>1</sup>

Mounting set white aluminium

IP20

206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm

## LED

6500 K

CRI ≥ 80

## Optical

emergency light

beam angle 21°<sup>2</sup>, 103°x25°<sup>3</sup>, 149°x150°<sup>4</sup>

## Electrical

system 1.0 W

inset 1.0 W

200 mA

PC2 220-240V

system 206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm/W<sup>5</sup>

inset 206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm/W<sup>6</sup>

## Physical

trimless for exposed concrete ceiling

length 230 mm

width 230 mm

height 162 mm

2.41 kg

## Cutout

recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Spot lens <sup>3</sup> Escape route lens <sup>4</sup> Anti panic lens  
<sup>5</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>6</sup> incl. optical losses

## Installation instructions



## Lighting calculator

