

# SASSO 60 round wallwasher/floor

trim

048-2641619W 048-2696317 002-90771



Project / Type

Notes

Count / Date



### General

Ceiling , Recessed

rotation 360°

gold , RAL260-M <sup>1</sup>

Mounting set traffic white

IP20

798 lm

### LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 94 , R<sub>f</sub>: 87 , R<sub>f(1-15)</sub>: 86

MR 0.8

MDER 0.72

### Optical

wallwasher floor

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

non DIM

system 9.7 W

inset 8.3 W

27 Vf

300 mA

PC2 220-240V

system 82 lm/W<sup>3</sup>

inset 97 lm/W<sup>4</sup>

### Physical

trim

diameter 80 mm

height 48 mm

0.21 kg

### Cutout

diameter 73 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 60 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator



# SASSO 60 round wallwasher/floor

trim

048-2641619W 048-2696317 002-90771



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000  | 40 000 | 50 000 |
|--------------------|------------------------------|--------|---|--------|--------|
| LLMF               | 0.96                         | 0.92   | 0.89  | 0.85   | 0.82   |
| LSF                | 1                            | 1      | 1   | 1      | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> Room Surface Maintenance Factor |        |        |
| MF                 | Maintenance Factor           |        | LLMF Lamp Lumens Maintenance Factor               |        |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF Lamp Survival Faktor                          |        |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 43                 |
| B13                            | 55                 |
| B16                            | 68                 |
| B20                            | 85                 |
| C10                            | 72                 |
| C13                            | 94                 |
| C16                            | 116                |
| C20                            | 145                |

## Components

### MOUNTING SET with trim 1 lamp

|                                   |                         |              |                                  |
|-----------------------------------|-------------------------|--------------|----------------------------------|
| TYPE<br>for intermediate ceilings | COLOUR<br>traffic white | Ø (MM)<br>80 | ARTICLE NUMBER(S)<br>048-2696317 |
|-----------------------------------|-------------------------|--------------|----------------------------------|



### CONVERTER

|              |                        |                                |
|--------------|------------------------|--------------------------------|
| TYPE<br>13 W | L·W·H (MM)<br>85·40·22 | ARTICLE NUMBER(S)<br>002-90771 |
|--------------|------------------------|--------------------------------|



## Mounting accessories

### PRIMED CONCRETE MOUNTING HOUSING

|                           |                           |                                  |
|---------------------------|---------------------------|----------------------------------|
| COLOUR<br>white aluminium | L·W·H (MM)<br>614·307·120 | ARTICLE NUMBER(S)<br>048-2695110 |
|---------------------------|---------------------------|----------------------------------|



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

|               |                        |                                  |
|---------------|------------------------|----------------------------------|
| TYPE<br>160 W | L·W·H (MM)<br>72·90·63 | ARTICLE NUMBER(S)<br>005-6520210 |
|---------------|------------------------|----------------------------------|



### DIN RAIL LED DRIVER

|  |                        |                                  |
|--|------------------------|----------------------------------|
| TYPE<br>DALI-2   200-1050 mA   2 x 42W | L·W·H (MM)<br>36·88·59 | ARTICLE NUMBER(S)<br>005-6121030 |
|--|------------------------|----------------------------------|

