

# SASSO 60 round wallwasher

trimless


048-2641511A 048-2696117 002-90762



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
 rotation 360°  
 black , RAL9005 <sup>1</sup>  
 Mounting set traffic white  
 IP20  
 700 lm

## LED

3000 K  
 CRI ≥ 90  
 L80 / 50000 h  
 initial MacAdam ≤ 3 SDCM  
 R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89  
 MR 0.6  
 MDER 0.54

## Optical

wallwasher  
 PstLM ≤ 1.0 <sup>2</sup>  
 SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
 system 9.7 W  
 inset 8.3 W  
 27 Vf  
 300 mA  
 PC2 220-240V  
 system 72 lm/W<sup>3</sup>  
 inset 85 lm/W<sup>4</sup>  
 1 DALI Addr.

## Physical


trimless  
 diameter 73 mm  
 height 48 mm  
 0.28 kg

## Cutout

diameter 73 mm  
 recessed depth 120 mm

Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

## Installation instructions



## Lighting calculator

