

SASSO 60 square downlight

trim 2 lamps



048-2612619M 048-2699317 002-90762



Project / Type

Notes

Count / Date



General

Ceiling , Recessed
gold , RAL260-M¹
Mounting set traffic white
front IP44 , back IP20
2020 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 97 , R_r: 90 , R₍₁₋₁₅₎: 89
MR 0.81
MDER 0.74

Optical

medium
beam angle 21°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0²
SVM ≤ 0.4²

Electrical

DALI-2
25.2 W
inset 10.7 W
36 Vf
300 mA
total insets 21.4 W
PC2 220-240V
80 lm/W
1 DALI Addr.

Physical


trim
length 147 mm
width 81 mm
height 48 mm
0.34 kg

Cutout


length 138 mm
width 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[048-2612619M 048-2699317 002-90762] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

22.07.2024

1 / 1