

# SASSO PRO 100

## adjustable offset trim round

048-2413417M 052-1932448



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling , Recessed  
 tilt max 35°  
 rotation 360°  
 white , RAL9016 <sup>1</sup>  
 Mounting set jet black  
 IP20  
 2560 lm

### LED

2700 K  
 CRI ≥ 90  
 L90 / 50000 h  
 initial MacAdam ≤ 3 SDCM  
 R<sub>g</sub>: 101, R<sub>r</sub>: 94, R<sub>{1-15}</sub>: 95  
 MR 0.55  
 MDER 0.5

### Optical

medium  
 beam angle 26°  
 P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>  
 SVM ≤ 0.4 <sup>2</sup>

### Electrical

non DIM  
 27.0 W  
 PC2 220-240V  
 95 lm/W

### Physical


trim  
 diameter 112 mm  
 height 106 mm  
 0.59 kg

### Cutout


diameter 108 mm  
 min. ceiling thickness 5 mm  
 max. ceiling thickness 25 mm  
 recessed depth 130 mm

Round recessed spotlight in die-cast aluminium with recessed luminaire plane; surface white powder coated; 360° rotatable and 35° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 5-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality reflector made of plastic with spherical reflector; aluminium, vapour deposition coated; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 26° beam; installed and exchanged without tools; optical attachments available as accessories; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. converter, non dimmable; converter wired secondary side; through wiring connection box, 3-pole or 5-pole, available as an accessory; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



medium 26°

h (m)	E0° (lx)	ø (m)
1	8620	0.47
2	2150	0.93
3	960	1.40
4	540	1.86
5	340	2.33

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Installation instructions



### Lighting calculator

