

SASSO PRO 100

adjustable offset trim square

048-2412617W 052-1952417



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|-------------------------------|--|
| Ceiling , Recessed | |
| tilt max 35° | |
| rotation 360° | |
| white , RAL 9016 ¹ | |
| Mounting set traffic white | |
| IP20 | |
| 2280 lm | |

LED

| | |
|--|--|
| 4000 K | |
| CRI ≥ 90 | |
| L80 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 97 , R _r : 89 , R ₍₁₋₁₅₎ : 91 | |
| MR 0.85 | |
| MDER 0.77 | |

Optical

| | |
|---------------------------------------|--|
| wide flood | |
| beam angle 57° | |
| P _{st} LM ≤ 1.0 ² | |
| SVM ≤ 0.4 ² | |

Electrical

| | |
|-----------------------------|--|
| non DIM | |
| 220-240 V | |
| system 27.0 W | |
| system 84 lm/W ³ | |
| PC2 | |

Physical


| | |
|---------------|--|
| trim | |
| length 112 mm | |
| width 112 mm | |
| height 106 mm | |
| 0.63 kg | |

Cut out


| | |
|------------------------------|--|
| diameter 108 mm | |
| min. ceiling thickness 5 mm | |
| max. ceiling thickness 25 mm | |
| recessed depth 130 mm | |

Round recessed spotlight in die-cast aluminium with recessed luminaire plane; surface white powder coated; 360° rotatable and 35° tiltable; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim traffic white; suitable for ceiling thickness of 5-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality reflector made of plastic with spherical reflector; aluminium, vapour deposition coated; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 57° beam; installed and exchanged without tools; optical attachments available as accessories; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; converter wired secondary side; through wiring connection box, 3-pole or 5-pole, available as an accessory; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

