

SASSO PRO 80 adjustable offset trim round

048-2310518V 052-1932328



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

tilt max 35°

rotation 360°

black , RAL 9005 ¹

Mounting set jet black

IP20

379 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98 , R_r: 91 , R₍₁₋₁₅₎: 89

MR 0.6

MDER 0.55

Optical

super spot

beam angle 8°

UGR < 10

Electrical

non DIM

220-240 V

system 7.7 W

system 49 lm/W²

PC2

Physical

trim

diameter 98 mm

height 83 mm

0.43 kg

Cutout

diameter 92 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 130 mm

Round recessed spotlight in die-cast aluminium with recessed luminaire plane; surface black powder coated; 360° rotatable and 35° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with high power LED for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 8° beam; optical attachments available as accessories; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; converter wired secondary side; through wiring connection box, 3-pole or 5-pole, available as an accessory; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code

² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

