

# MINO 60 CIRCLE 1000

## direct / indirect

suspended  
034-241353XH



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Suspended	
special colours	
IP20	
indirect 3010 lm	
direct 6570 lm	
total 9580 lm	

### LED

3000 K	
CRI ≥ 80	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.56	
MDER 0.51	

### Optical

High Performance Opal	
opal (lambertsch)	
PstLM ≤ 1.0 <sup>1</sup>	
SVM ≤ 0.4 <sup>1</sup>	

### Electrical

DALI-2	
220-240 V	
system 71 W	
PC1	
system 135 lm/W <sup>2</sup>	
5 DALI Addr.	


### Physical

cable 1500 mm / canopy central	
diameter 1060 mm	
height 80 mm	
centerline radius 500 mm	
9 kg	


<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; suspended luminaire with 1500mm cable suspension (canopy central); with integrated toolless suspension height adjustment on the luminaire; incl. feed (white); surface special colours powder coated; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; direct/indirect light emission for additional accentuation of the ceiling; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

