

# MINO 60 CIRCLE 1000

direct / indirect

suspended

034-2413537H



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

white , RAL 9010 <sup>1</sup>

IP20

indirect 3010 lm

direct 6570 lm

total 9580 lm

## LED

3000 K

CRI  $\geq$  80

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

MR 0.56

MDER 0.51

## Optical

High Performance Opal

opal (lamberts)

PstLM  $\leq$  1.0<sup>2</sup> <sup>3</sup>

SVM  $\leq$  0.4<sup>2</sup> <sup>3</sup>

## Electrical

DALI-2

220-240 V

system 71 W

system 135 lm/W<sup>4</sup>

PC1

5 DALI Addr.

## Physical

cable 1500 mm / canopy central

diameter 1060 mm

height 80 mm

centerline radius 500 mm


9 kg

<sup>1</sup> RAL code <sup>2</sup> combined


<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



## Product drawing



\*canopy central version

