

MINO 60 CIRCLE 1500

direct / indirect

suspended

034-241163XH



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

IP20

indirect 5490 lm

direct 12000 lm

total 17500 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

High Performance Opal

opal (lambertsch)

PstLM $\leq 1.0^{1,2}$

SVM $\leq 0.4^{1,2}$

Electrical

DALI-2

220-240 V

system 114 W

system 154 lm/W³

PC1

5 DALI Addr.

Physical

cable 1500 mm / canopy central

diameter 1560 mm

height 80 mm


centerline radius 750 mm

14 kg


¹ combined ² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



*canopy central version

Installation instructions



Lighting calculator



[034-241163XH] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

04.04.2025