

# MINO 60 CIRCLE 1500

## direct / indirect

suspended  
034-2211537Z



Project / Type	
Notes	
Count / Date	



RG0 IEC 62471	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

### General

Ceiling , Suspended
white , RAL9010 <sup>1</sup>
IP20
indirect 4820 lm
direct 9130 lm
total 13950 lm

### LED

3000 K
CRI ≥ 80
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
MR 0.56
MDER 0.51

### Optical

Microprismatic
microprismatic
UGR < 19
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

### Electrical


DALI-2
system 114 W
PC1 220-240V
system 122 lm/W <sup>3</sup>
5 DALI Addr.

### Physical


cable 1500 mm
diameter 1560 mm
height 80 mm
centerline radius 750 mm
13 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

