

MINO CIRCLE ACOUSTIC

1500

ceiling
034-271211W



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



| |
|-------------------|
| General |
| Ceiling , Surface |
| white |

| |
|------------------|
| Physical |
| diameter 1434 mm |
| height 24 mm |
| 8.4 kg |

| |
|---|
| Acoustics |
| Alpha w (α_w) up to 0.7 ¹ |
| SAC (sound absorption class) up to C ¹ |
| NRC up to 1.15 ¹ |
| SAA up to 1.16 ¹ |


¹ Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; round design; high quality visual and tactile surface, white; colour may deviate; absorption of direct sound; this creates high acoustic performance; for ceiling surface mounting;

Product drawing



MINO CIRCLE ACOUSTIC 1500

ceiling
034-271211W



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

| 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ |
|--------|--------|--------|---------|---------|---------|
| 0.3 | 0.6 | 1.43 | 2.3 | 2.17 | 2.1 |

Sound absorption coefficient (α_p)

