

# MINO CIRCLE ACOUSTIC 1500

inlay  
034-270211L



Project / Type

Notes

Count / Date



General

Luminaire / Track , Mounted

black

Physical

diameter 1434 mm

height 24 mm

6.2 kg

Acoustics

Alpha w ( $\alpha_w$ ) up to 0.65 <sup>1</sup>

SAC (sound absorption class) up to C <sup>1</sup>

NRC up to 0.7 <sup>1</sup>

SAA up to 0.74 <sup>1</sup>


<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

## Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 50% recycled PET; round design; high quality visual and tactile surface, black; colour may deviate; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for insertion into the MINO 60 CIRCLE 1500 ceiling or MINO 60 CIRCLE 1500 suspended;

## Product drawing



[‘034-270211L’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)