

UNICO wall 1 lamp

surface


090-0L161TG001



Project / Type

Notes

Count / Date



General

Wall , Surface

grey , RAL9006 ¹

IP20

244 lm

LED

4000 K

CRI \geq 90

L90 / 50000 h

initial MacAdam \leq 3 SDCM

MR 0.89

MDER 0.81

Optical

asymmetric

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

non DIM

system 5.8 W

PC1

system 42 lm/W³

Physical

length 52 mm


width 53 mm

height 96 mm

0.35 kg

Rectangular wall surface mounted uplight made of aluminium; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface grey powder coated; equipped with one light inset; high quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 90% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC1; suitable for through wiring; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions

