

# SASSO 100 round wallwasher

trim

048-2740417A 048-279631G 002-90776



Project / Type
Notes
Count / Date



--	--	--	--	--

## General

Ceiling , Recessed
rotation 360°
white , RAL9016 <sup>1</sup>
Mounting set white aluminium
IP20
2050 lm

## LED

2700 K
CRI ≥ 90
L70 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 90
MR 0.53
MDER 0.48

## Optical

wallwasher
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2
29.4 W
inset 25.0 W
36 Vf
350 mA
PC2 220-240V
70 lm/W
inset 82 lm/W

## Physical


trim
diameter 118 mm
height 96 mm
0.69 kg

## Cutout

diameter 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 120 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

