

SASSO 100 square wallwasher/floor

trim

048-2750519W 048-279731G 002-90776



Project / Type

Notes

Count / Date



General

Ceiling , Recessed
gold , RAL260-M¹
Mounting set silver-grey
IP20
2670 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
 $R_g: 100$, $R_f: 91$, $R_{f(1-15)}: 88$
MR 0.59
MDER 0.53

Optical

wallwasher floor
 $P_{stLM} \leq 1.0^2$
 $SVM \leq 0.4^2$

Electrical

DALI-2
27.5 W
inset 23.4 W
36 Vf
700 mA
PC2 220-240V
97 lm/W

Physical

trim
length 118 mm
width 118 mm
height 96 mm
0.73 kg

Cutout


length 112 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions




Lighting calculator



Recessed square spotlight in die-cast aluminium; 1 lamp; surface gold; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim silver-grey; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

