

LINEA inner corner opal / asymmetric

wall system
058-6111638AA



Project / Type _____


Notes _____

Count / Date _____




Light fitting and front cover made of extruded aluminium profile; angular design; 90° corner element - inner corner; for lighting systems; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct light component: HPO (High Performance Opal) cover for uniform illumination; indirect light component: with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling / Wall , Surface _____

black , RAL9005 ¹ _____

3520 lm/m _____

IP20 _____

indirect 2310 lm _____

direct 1940 lm _____

total 4250 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_f: 90 , R_{f(1-15)}: 88 _____

MR 0.76 _____

MDER 0.69 _____

Optical

High Performance Opal / Asymmetric _____

asymmetric _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

35 W _____

PC1 220-240V _____

121 lm/W _____

29 W/m _____

Physical

length 633 mm _____

width 633 mm _____

height 100 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

