

TASK

table base plate

059-2811770 059-2891117



Project / Type
Notes
Count / Date



General

Table , Standing
tilt min -15°
tilt max 15°
rotation 360°
white , RAL 9010 ¹
Mounting pure white
IP20
1010 lm

LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 96 , R _r : 90 , R _{t-15} : 87
MR 0.75
MDER 0.68

Optical

Opal
opal (lambertsch)

Electrical

touch DIM & presence sensor
220-240 V
system 11.0 W
system 92 lm/W ²
PC2

Physical

base plate
length 227 mm
width 120 mm
height 880 mm
5 kg


¹ RAL code
² FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions




Desk lamp in puristic design, with rectangular lamp head with rounded edges in aluminium; extremely flat design (only 15mm); lamp head 360° rotatable and +/- 15° tiltable; lamp arm with 3 joints for maximum flexibility; surface white powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; opal PMMA cover; completely homogeneous illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; continuously adjustable dimming via optical sensor (10-100% analog); presence detector; integrated USB charging socket for charging of a smart device; external power supply for converter with power plug; incl. base plate; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



TASK

table base plate
059-28111770 059-2891117



Project / Type

Notes

Count / Date

Components

BASE PLATE

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
pure white	220	059-2891117

