

SASSO 60 round wallwasher/floor

trimless exposed concrete

048-2641419W 048-2695210 002-90762



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 rotation 360°
 gold , RAL260-M¹
 Mounting set white aluminium
 IP20
 739 lm

LED

2700 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 97 , R_f: 91 , R₍₁₋₁₅₎: 90
 MR 0.53
 MDER 0.48

Optical

wallwasher floor
 PstLM ≤ 1.0²
 SVM ≤ 0.4²

Electrical

DALI-2
 9.7 W
 inset 8.3 W
 27 Vf
 300 mA
 PC2 220-240V
 76 lm/W
 inset 90 lm/W
 1 DALI Addr.

Physical

trimless for exposed concrete ceiling
 length 230 mm
 width 230 mm
 height 162 mm
 2.41 kg


Cutout

recessed depth 120 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

