

SASSO 60 round wallwasher/floor

trimless exposed concrete

048-2641419W 048-2695210 002-90762



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____
 rotation 360° _____
 gold , RAL260-M ¹ _____
 Mounting set white aluminium _____
 IP20 _____
 739 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 L80 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 97 , R_f: 91 , R₍₁₋₁₅₎: 90 _____
 MR 0.53 _____
 MDER 0.48 _____

Optical

wallwasher floor _____
 PstLM ≤ 1.0 ² _____
 SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____
 9.7 W _____
 inset 8.3 W _____
 27 Vf _____
 300 mA _____
 PC2 220-240V _____
 76 lm/W _____
 inset 90 lm/W _____
 1 DALI Addr. _____

Physical

trimless for exposed concrete ceiling _____
 length 230 mm _____
 width 230 mm _____
 height 162 mm _____
 2.41 kg _____


Cutout

recessed depth 120 mm _____


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator



SASSO 60 round wallwasher/floor

trimless exposed concrete

048-2641419W 048-2695210 002-90762



Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B16	30
C10	23
C16	36

Components

EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	230-230-162	048-2695210



CONVERTER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
28 W	143-43-30	002-90762



Optional electrical accessories

DIN RAIL POWER SUPPLY

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
160 W	72-90-63	005-6520210



DIN RAIL LED DRIVER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
DALI-2 200-1050 mA 2 x 42W	36-88-59	005-6121030

