

# INO 1200 circle acoustic

luminaire mounted  
034-370411X



Project / Type \_\_\_\_\_  
Notes \_\_\_\_\_  
Count / Date \_\_\_\_\_



## General

Luminaire / Track , Mounted \_\_\_\_\_  
acoustic special colours \_\_\_\_\_

## Physical

diameter 1050 mm \_\_\_\_\_  
height 9 mm \_\_\_\_\_  
1.06 kg \_\_\_\_\_

## Acoustics

Alpha w ( $\alpha_w$ ) 0.6 <sup>1</sup> \_\_\_\_\_  
SAC (sound absorption class) C <sup>1</sup> \_\_\_\_\_  
NRC 0.55 <sup>1</sup> \_\_\_\_\_  
SAA 0.57 <sup>1</sup> \_\_\_\_\_

<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

## Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 50% recycled PET; round design; high quality visual and tactile surface, acoustic special colours; colour may deviate; for mounting on the INO circle suspended cable suspensions, above the luminaire; subsequent attachment possible;

# INO 1200 circle acoustic

luminaire mounted  
034-370411X



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.63	0.57	0.83	0.97	1.2	1.37

## Sound absorption coefficient ( $a_p$ )

