

TASK direct / indirect power

free standing double
X059-2962056Z



Project / Type	
Notes	
Count / Date	



General

Floor , Standing	
grey , RAL 9006 ¹	
IP20	
indirect 14700 lm	
direct 4800 lm	
total 19500 lm	

LED

3000 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 96 , R _f : 90 , R _{t(1-15)} : 90	
MR 0.61	
MDER 0.56	

Optical

Microprismatic	
microprismatic	
UGR ≤ 13 , ≥65° <3000 cd/m ²	
P _{stLM} ≤ 1.0 ^{2 3}	
SVM ≤ 0.4 ^{2 3}	

Electrical

touch DIM on pole	
220-240 V	
system 161 W	
system 121 lm/W ⁴	
PC1	

Physical

U-shape	
length 800 mm	
width 940 mm	
height 2054 mm	
13.5 kg	


¹ RAL code ² combined
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Free standing luminaire with two rectangular luminaire head made of aluminium and rounded edges; luminaire heads arranged parallel; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base (U-shape); surface grey powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

