

MITA circle 450 reflector

direct / indirect soft

ceiling

074-7531637R




| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |




Ring-shaped light fitting in die-cast aluminium; extremely slim design; surface white powder coated; luminaire housing set away from ceiling; electronic operating unit installed in the surface mounted housing: surface mounted housing aligned from the ring to the center; blind cover to cover the cut-out, held by magnet, available as an accessory; accessories are listed separately; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high gloss reflector with faceted design; Reflector chrome; UGR ≤ 19 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 1500$ cd/m²; direct / indirect radiation characteristic for additional accentuation of the ceiling; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|-------------------------------|
| Ceiling , Surface |
| white , RAL 9016 ¹ |
| Reflector chrome |
| IP20 |
| indirect 82 lm |
| direct 4800 lm |
| total 4880 lm |

LED

| |
|-------------------------------|
| 4000 K |
| CRI ≥ 80 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| MR 0.72 |
| MDER 0.65 |

Optical

| |
|---|
| Reflector |
| symmetric |
| UGR < 19 , $\geq 65^\circ < 1500$ cd/m ² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|------------------------------|
| DALI-2 |
| 220-240 V |
| system 30 W |
| system 163 lm/W ³ |
| PC1 |
| 1 DALI Addr. |

Physical

| |
|-----------------|
| diameter 426 mm |
| height 72 mm |

¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

