

BETO direct / indirect power

free standing U-shape

074-6954518B



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|-------------------------------|--|
| Floor , Standing | |
| black , RAL 9005 ¹ | |
| Reflector dark chrome | |
| IP20 | |
| indirect 6630 lm | |
| direct 1490 lm | |
| total 8120 lm | |

LED

| | |
|--------------------------|--|
| 3000 K | |
| CRI ≥ 80 | |
| L90 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| MR 0.56 | |
| MDER 0.51 | |

Optical

| | |
|--------------------------|--|
| Reflector | |
| asymmetric | |
| UGR ≤ 10 | |
| PstLM ≤ 1.0 ² | |
| SVM ≤ 0.4 ² | |

Electrical


| | |
|------------------------------|--|
| touch DIM on pole | |
| 220-240 V | |
| system 66 W | |
| system 123 lm/W ³ | |
| PC1 | |

Physical


| | |
|----------------|--|
| U-shape | |
| length 1055 mm | |
| width 42 mm | |
| height 2100 mm | |

Free standing luminaire from extruded aluminium profile in angular design; extremely slim design (only 42 x 42 mm); square downpipe; pedestal with recess for table base (U-shape); surface black powder coated; direct/indirect illumination characteristic; direct light component with high gloss reflector + faceted design and asymmetric radiation characteristic; Reflector dark chrome; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; UGR ≤ 10; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



BETO direct / indirect power

free standing U-shape

074-6954518B



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |

MF

LMF × RSMF × LLMF × LSF

MF

Maintenance Factor

LMF^a

Luminaire Maintenance Factor

RSMF^a

Room Surface Maintenance Factor

LLMF

Lamp Lumens Maintenance Factor

LSF

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 13 |
| B13 | 17 |
| B16 | 21 |
| B20 | 27 |
| C10 | 21 |
| C13 | 28 |
| C16 | 35 |
| C20 | 45 |

