

SASSO 60 round adjustable ceiling 048-31104374W



Project / Type _____

Notes _____

Count / Date _____



General
Ceiling , Surface
tilt max 30°
rotation 360°
white , RAL9016/matt silver ¹
Inner colour matt silver
IP20
855 lm


LED
2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.53
MDER 0.48

Optical
wide flood
beam angle 54°
≥65° <3000 cd/m²

Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface white (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 54° beam; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical
DALI-2
10.4 W
PC1 220-240V
82 lm/W
inset 97 lm/W
1 DALI Addr.

Light distribution



Product drawing



Physical
diameter 72 mm
height 108 mm
0.5 kg

¹ RAL code

Installation instructions



Lighting calculator

